



DECLARATION OF PERFORMANCE

N° 85/1

<b>Identification Code</b>	68 - VERTIGO
<b>Intended use:</b>	Slabs for external paving
<b>Harmonised standard:</b>	UNI EN 1341-2013
<b>Manufacturer:</b>	Petra Antiqua srl Via Giovanni XXIII, 72 - Monte di Malo (VI) tel. 0445/585658 fax. 0445/607492
<b>Evaluation system in procedure:</b>	4
<b>Italian certifying agency:</b>	

Features	Harmonised standard, mandated levels and/or classes
Petrographic definition (UNI EN 12407:03):	biomicrite dolomitizzata
Flexural strength under concentrated load (UNI EN 12372:07):	
Flexural strength (lower expected value):	12,5 MPa
Flexural strength (mean value):	15,1 MPa
Standard deviation:	1,28
(After freeze/thaw cycles UNI EN 12371:10):	
Flexural strength (lower expected value):	11,8 MPa
Flexural strength (mean value):	14,3 MPa
Standard deviation:	1,19
Variation of value of flexural strenght after freeze/thaw cycles:	
Water absorption at atmospheric pressure (UNI EN 13755:08)	3,1%
Slip resistance (USRV - UNI EN 1341:03 App. D):	59
Abrasion resistance (UNI EN 14157-03:2005 metodo A):	21,0 mm

The performance of the product referred to the points 1 and 2 is conforming to the stated performance set out in point 9. This declaration of performance is issued under the exclusive responsibility of the manufacturer identified in point 4.

Petra Antiqua srl  
L' Amministratore  
Roberto Bressan

Monte di Malo, 01 October 2019



DECLARATION OF PERFORMANCE

N° 86/1

<b>Identification Code</b>	68 - VERTIGO
<b>Intended use:</b>	Slabs of natural stone for use as cladding for outside or inside
<b>Harmonised standard:</b>	UNI EN 1469:2005
<b>Manufacturer:</b>	Petra Antiqua srl Via Giovanni XXIII, 72 - Monte di Malo (VI) tel. 0445/585658 fax. 0445/607492
<b>Evaluation system in procedure:</b>	4
<b>Italian certifying agency:</b>	

Features	Harmonised standard, mandated levels and/or classes
Petrographic definition (UNI EN 12407:03):	biomicrite dolomitizzata Classe A1
Reaction to fire (value declared in according to Comminssion Decision 96/603/EC):	
Flexural strength under concentrated load (UNI EN 12372:07):	
Flexural strength (lower expected value):	12,5 MPa
Flexural strength (mean value):	15,1 MPa
Standard deviation:	1,28
(After freeze/thaw cycles UNI EN 12371:10):	
Flexural strength (lower expected value):	11,8 MPa
Flexural strength (mean value):	14,3 MPa
Standard deviation:	1,19
Variation of value of flexural strenght after freeze/thaw cycles:	
Breaking load at dowel hole (UNI EN 13364:03)	
Flexural strength (lower expected value):	
Flexural strength (mean value):	
Standard deviation:	
Water absorption at atmospheric pressure (UNI EN 13755:08)	3,1%
Apparent density (UNI EN 1936:07) (mean value)	2460 Kg./m <sup>3</sup>

The performance of the product referred to the points 1 and 2 is conforming to the stated performance set out in point 9. This declaration of performance is issued under the exclusive responsibility of the manufacturer identified in point 4.

Petra Antiqua srl  
L' Amministratore  
Roberto Brassan

Monte di Malo, 01 October 2019



DECLARATION OF PERFORMANCE

N° 87/1

<b>Identification Code</b>	68 - VERTIGO
<b>Intended use:</b>	Flat modular tiles of natural stone for use as cladding
<b>Harmonised standard:</b>	UNI EN 12057:2005
<b>Manufacturer:</b>	Petra Antiqua srl Via Giovanni XXIII, 72 - Monte di Malo (VI) tel. 0445/585658 fax. 0445/607492
<b>Evaluation system in procedure:</b>	4
<b>Italian certifying agency:</b>	

<b>Features</b>	<b>Harmonised standard, mandated levels and/or classes</b>
Petrographic definition (UNI EN 12407:03):	biomicrite dolomitizzata Classe A1
Reaction to fire (value declared in according to Commission Decision 96/603/EC):	
Flexural strength under concentrated load (UNI EN 12372:07):	
Flexural strength (lower expected value):	12,5 MPa
Flexural strength (mean value):	15,1 MPa
Standard deviation:	1,28
(After freeze/thaw cycles UNI EN 12371:10):	
Flexural strength (lower expected value):	11,8 MPa
Flexural strength (mean value):	14,3 MPa
Standard deviation:	1,19
Variation of value of flexural strength after freeze/thaw cycles:	
Water absorption at atmospheric pressure (UNI EN 13755:08)	3,1%
Apparent density (UNI EN 1936:07) (mean value)	2460 Kg./m <sup>3</sup>

The performance of the product referred to the points 1 and 2 is conforming to the stated performance set out in point 9. This declaration of performance is issued under the exclusive responsibility of the manufacturer identified in point 4.

Petra Antiqua srl  
L' Amministratore  
Roberto Bressan

Monte di Malo, 01 October 2019



DECLARATION OF PERFORMANCE

N° 88/1

<b>Identification Code</b>	68 - VERTIGO
<b>Intended use:</b>	Flat natural stone slabs fabricated for use as floor and stair coverings for outside use
<b>Harmonised standard:</b>	UNI EN 12058:2005
<b>Manufacturer:</b>	Petra Antiqua srl Via Giovanni XXIII, 72 - Monte di Malo (VI) tel. 0445/585658 fax. 0445/607492
<b>Evaluation system in procedure:</b>	4
<b>Italian certifying agency:</b>	

Features	Harmonised standard, mandated levels and/or classes
Petrographic definition (UNI EN 12407:03):	biomicrite dolomitizzata Classe A1
Reaction to fire (value declared in according to Commission Decision 96/603/EC):	
Flexural strength under concentrated load (UNI EN 12372:07):	
Flexural strength (lower expected value):	12,5 MPa
Flexural strength (mean value):	15,1 MPa
Standard deviation:	1,28
(After freeze/thaw cycles UNI EN 12371:10):	
Flexural strength (lower expected value):	11,8 MPa
Flexural strength (mean value):	14,3 MPa
Standard deviation:	1,19
Variation of value of flexural strength after freeze/thaw cycles:	
Slip resistance SRV (UNI EN 14231:04)	
SRV "dry - Surface finish: WAX FINISHED":	50
SRV "wet - Surface finish: WAX FINISHED":	19
Thermal shock resistance (UNI EN 14066:04)	N.P.D.

The performance of the product referred to the points 1 and 2 is conforming to the stated performance set out in point 9. This declaration of performance is issued under the exclusive responsibility of the manufacturer identified in point 4.

Petra Antiqua srl  
L' Amministratore  
Roberto Brassan

Monte di Malo, 01 October 2019